

# **ENCROACHMENT PERMIT**



PERMIT MUST BE AVAILABLE FOR REVIEW & INSPECTION AT ALL TIMES AT THE PERMITTED WORKSITE

			GENER	AL PERMIT I	NFORMATION					
Issuance Date	UDOT Region	Inspection Billing Number		r W.O	. Number (applicant-p	rovided)	OLP Application ID			
8/15/2017		81R03172			MC16802		79480			
State Route	Milepost Start	Latitude	Longitue	de		Worksite Ac	e Address			
0028	26,233	39.5057924712025	-111.8723701	135583		SR 28				
Permittee		tee Name	Pr	imary Contact	Primary I	hone	Email			
Information	Cen	traCom	Cent	ral Utah Telephone	(435) 427-	3331	p.rigby@cut	net		
Work Being		Compa	ny Name		Primary P	hone	Email			
erformed for	Central Utah Telephone				(435) 427-	(435) 427-3331		pamrigby@centracom.com		
Emergency		Contac	ct Name		Primary P	hone	Email			
Field Contact	d Contact // Pat Coates			cant-Provided)	(435) 427-3331		pamrigby@centracom.com			
			PERMITAL	THORIZATIO	N TIME-FRAMES		SULA Confirmatio	n Number		
Start	08/21/2017	Expires	09/20/20	17	Total Day Count	UNIVERSE OF THE PARTY OF THE PA	30			
Work Only Aut	Service productions and a service service and a form	Mondays	Tuesdays	Wednesdays	Thursdays	Fridays	Saturdays	Sundays		
Applicant must refer to the TC&L table (p.2 of this permit)					Start Time:		Completed By:			
for spe	time authorization	on instructions.		Start Time:		Completed By:				
	Please en	ail the following ind	lividual 24-ho	urs before work v	menced within UDOT vill start. tion Notice (insert App					

An Encroachment Permit is hereby authorized subject to Utah Administrative Code R930-6, R930-7, and any other applicable laws or regulations. By performing the activities authorized by this permit, the permittee agrees to strictly comply with all permit terms, conditions, and limitations (TC&L's), including any attachments submitted with the application. Failure to abide by all permit TC&L's, or any term set forth by this permit, is grounds for immediate verbal stop work order, written stop work order, permit revocation, the restriction of future permits, or other legal or equitable remedies.

In the event work is commenced under this permit and the permittee fails or refuses to complete the work, including performing substandard work, UDOT may, at its discretion, order the permittee to stop work and UDOT may correct any deficiencies or otherwise complete the permitted work at the expense of the permittee. Upon the receipt of an invoice for any costs, including all inspection costs, incurred by UDOT, the permittee shall immediately pay the amount due. If an action is required to be filed in court to collect the amount due, the permittee shall be liable for UDOT's costs and fees, including attorney fees. The permittee will strictly comply with the traffic control standards and warn the public of said work within UDOT's right-of-way to protect the traveling public and all personnel authorized within the permitted work zone. When traffic control is required, the permittee will not pre-stage any vehicles, equipment, personnel, or materials within any portion of UDOT's right-of-way until the required traffic control is in place. By accepting this permit, the permittee shall defend, indemnify, and hold harmless UDOT, its employees, consultants, contractors, agents, and the State of Utah, from all damages or claims, including attorney fees, arising out of the work performed under this permit by permittee, permittee's employees, agents, consultants, contractors, or subcontractors.

Authorizing Name (printed): Stuart Hoff Authorizing Name (signed):

Strong Hoff



### **ENCROACHMENT PERMIT**



#### Listed Subcontractors

Application Step 3 of 5 Responses	Application Step 4 of 5 Responses				
New or Existing Utility Work within UDOT's Right-of-Way	- NATURE OF FACILITY	( <del></del>	Buried		
NO Travel Lane Impacts	- UTILITY TRANSMISSION TY	PE —	Telecommunication s/Fiber		
	- NATURE OF WORK	$- \frac{1}{2}$	New Installation		
	- NATURE OF WORK	2	Casing or Conduit		
	- NATURE OF WORK	_	Casing/Conduit Size Diameter	1.25	
	- INSTALLATION METHOD	_	Boring or Direction Drilling		
	- INSTALLATION METHOD	-	Plowing		
	- INSTALLATION METHOD		Plow Depth	5'	
	- SURFACE TYPE	_	Other (Explain)	dirt	

# The following document were electronically uploaded in the Online Permit System and are associated with this permit: Document Type: Document Name: Liability Insurance UDOT insurance cert 2017.pdf Traffic Control Plan Levan Peak 2.jpg.pdf Traffic Control Plan Levan Peak 1.jpg.pdf Detail Plan of Work CentraCom\_MC16802\_LevanPeakHwyConduit.pdf Bond R930-7 Statewide Performance and Warranty Bond UDOT.pdf

#### SPECIAL LIMITATIONS

#### Restore ROW to original or better condition

#### PERMIT TERMS, CONDITIONS, AND LIMITATIONS

- 1. UDOT has the right to require an approved crash barrier to protect any above ground feature that is in UDOT right of way or AASTHO clear zone whichever is greater
- Contractors working in UDOT's right-of-way must maintain access to transit facilities. Contractor shall notify UTA of all bus stops within work zone at least 1 business day prior to placing traffic control. Contractor shall keep access to bus stops for both passengers and buses, or provide an alternative approved by UTA. Both preserved and alternate access must match existing conditions or meet ADA standards. UTA in Utah county Ken Anson 801.227.8957 or kanson@rideuta.com in Salt lake county contact Michael Clara 801.287.2325 or melara@rideuta.com in Weber County contact Bart Dean 801.287.1246 or bdean@rideuta.com. Bus stop access requirements may be waived by the UDOT permits officer on days when the bus does not run.
- INSPECTION CALL-IN REQUIREMENTS: The person performing the work authorized by the permit is responsible for notifying UDOT when work is ready for inspection.
   Every request for inspection must be called in at least 24-hours before the inspection is desired.
- 4. Pothole Utilities we will require core to be removed, locate utility, Flow fill to bottom of pavement, Put core back in and utilibond in place
- This agreement and/or permit is UDOT approval only. You are responsible to obtain clearances from rail roads, private propertyowners and local jurisdictions that you are working within.
- 6. Any asphalt damaged by your work will require a mill and overlay of the entire effected area with UDOT approved HMA mix design asphalt, from an approved source.
- If a contractor is working in the area of your permit scope. Contact contractor and work together so all work can be completed for all parties. Insure no traffic control conflicts
  exist. First contractor to start work has the right to complete their project first.
- If any potholes are required in the pavement you will be required to do them at Night from 9PM til 6AM No extensions will be allowed on this permit
- If any potholes are required in the pavement you will be required to do them at Night from 9PM til 6AM No extensions will be allowed on this permit
- 10. Licensee must do all work in accordance with UDOT standard drawings
- Use current edition of UDOT standard drawing for traffic control. Use Utah MUTCD standards for traffic control elements not shown in UDOT standard drawings. Traffic control must be posted at the encroachment site for entire encroachment period.
- Contact station foreman before starting project.
- 13. Prior to any work within the right-of-way, a traffic control plan must be submitted to UDOT and reviewed by the UDOT Traffic Engineer.
- 14. Traffic Control Plans, signs and channelizing devices must conform to MUTCD Standards, as a minimum, and all signs must be equipped with three orange flags.
- 15. This agreement and/or permit is UDOT approval only. You are responsible to obtain clearances from railroads, private property owners and local jurisdictions that you are working within.



## **ENCROACHMENT PERMIT**



#### PERMIT TERMS, CONDITIONS, AND LIMITATIONS

- 16. ANSI 107-2004 Class III clothing (or greater) is required of all workers within the right-of-way
- 17. Call 811, or contact Blue Stakes and check for other utilities in the area prior to excavation
- No saw or pavement cuts permitted on this job
- 19. Licensee must place material such as road base, slag, gravel, etc. a minimum of 6" thick between edge of pavement and property line to prevent tracking onto the highway.
- 20. ATSSA Certified Traffic Control Maintainer required.
- 21. Licensee must comply with all environmental issues to include cultural & paleontologist clearances (see attachment "F").
- 22. See Attachment "F"
- 23. Untreated Base Course with 97% compaction for the full depth of the trench with 6" lifts.
- 24. When a hazard is within the work clear zone and the vertical grade separation is 6" or greater or a slope steeper than 4:1, a UDOT approved barrier system is required.
- 25. If paving is done after Oct. 15 and before Apr. 15, licensee must replace temporary repair work when temperature and weather conditions are such that asphalt pavement can be placed in accordance with state specifications. In all instances, cold mix must be replaced with hot mix.
- 26. All work must comply with current ADA standards
- 27. Notify UDOT upon completion of project for inspection.
- 28. An inspector may be required at permittee's expense, with 48 hours notice. By accepting this permit, I agree to pay for inspection fees
- 29. Licensee is responsible for repairing and/or restoring any portion of the roadway damaged during construction.
- 30. Licensee must restore shoulder of highway to its original or better condition. Including reseeding, replacing sidewalk, fencing, pipe, culverts or signs removed or damaged during construction and any other roadway features.
- 31. All work must be completed by 12:00 PM prior to any Holiday and shall not commence until 8:00 AM on the following work day
- 32. Licensee shall keep highway free of mud and debris. A sweeper broom must be accessible for cleaning purposes
- 33. The depth of bury for all utility facilities under pavement shall be a minimum of four (4) feet below the top of pavement or existing grade including open drainage features. Where utility facilities are installed within 20 feet from the edge of pavement, the depth of bury shall be a minimum of five (5) feet below top of grade so as to allow for installation of UDOT signs or delineators. Utility facilities under sidewalks shall be installed a minimum of three (3) feet below the top of sidewalk.
- 34. No storage of backfill material or pipe will be allowed within the ASHTO Clear Zone. Excavations must be backfilled daily or barrier will be required
- 35 Permit Holder will comply with all applicable environmental laws
- 36. Upon completion of project, contact the inspector as listed on this permit
- 37. A copy of the permit must be present at the encroachment site for the entire encroachment period
- 38. By the accepting this permit, the Applicant acknowledges the hazardous nature of the work and agrees to assume full responsibility in the event of an accident or other incident involving death or injury to members of the Permitess Group or others, or property damage that results from negligence or intentional conduct on the part of any member of the group.